



"Superior Designs, Innovative Technology, Quality Materials"

- About Us
- Commitment
- Product News
- Contact Us

Home

Condensate Removal Pump Applications

- Furnace & A/C
- Dehumidifies
- Evaporative Coolers
- High efficiency Gas Furnaces
- Refrigeration

Condensate Pumps

Safety Switch

Condensate Removal Pump Features

- Patent pending thermal management
- Reliable performance
- Automated function

Wet-Rotor Pumps

Waterfall Pumps



direct result
pumps

111 Corporate Blvd. Suite
H South Plainfield, NJ
07080
| toll free: 888-755-4498

Model	Power Requirements			Tubing Included	Safety Switch	Max Lift	Tubing	Cord	Warranty	Height (in.)	Width (in.)	Length (in.)	Flow Rate
RC151	120 volts	60Hz	1.7 A	-	-	15'	3/8"	6'	1 year	6.5	5	11.17	94 GPH @1 ft.
RC151T	120 volts	60Hz	1.7 A	✓	-	15'	3/8"	6'	1 year	6.5	5	11.17	94 GPH @1 ft.
RC151S	120 volts	60Hz	1.7 A	-	✓	15'	3/8"	6'	1 year	6.5	5	11.17	94 GPH @1 ft.
RC151ST	120 volts	60Hz	1.7 A	✓	✓	15'	3/8"	6'	1 year	6.5	5	11.17	94 GPH @1 ft.
RC201	120 volts	60Hz	2.1 A	-	-	20'	3/8"	6'	1 year	6.5	5	11.17	114 GPH @1 ft.
RC201T	120 volts	60Hz	2.1 A	✓	-	20'	3/8"	6'	1 year	6.5	5	11.17	114 GPH @1 ft.
RC201S	120 volts	60Hz	2.1 A	-	✓	20'	3/8"	6'	1 year	6.5	5	11.17	114 GPH @1 ft.
RC201ST	120 volts	60Hz	2.1 A	✓	✓	20'	3/8"	6'	1 year	6.5	5	11.17	114 GPH @1 ft.
RC202S	230 volts	60Hz	1 A	-	✓	20'	3/8"	6'	1 year	6.5	5	11.17	114 GPH @1 ft.

p: 908.755.4498 f: 908.755.8326 info@directresultpumps.com

© Copyright 2008-2009 Direct Result Pumps. All Rights Reserved.