





## Air Filter Installation and Cleaning

Standard and custom sizes are available to fit any furnace. Install the filter by simply removing your existing disposable filter and sliding in your permanent new air filter. Furnaces with hammock style filter racks can be adapted easily. Check the system requirements for pressure drop/air velocity restrictions (i.e., Initial Resistance to Airflow 0.11 inches w.g.). These requirements can be found in the operating manual of the equipment.

Some of our air filter models are designed to have a directional air flow. Check the label on your filter frame before you install it. If the label does not have an air flow arrow, it means that the model design can be installed on either side. If the label does have an air flow arrow, it means that the filter is designed to be installed so that the air flows in the same direction, depending on how your HVACR system was designed to work.





Clean monthly by rinsing your filter with running water. Particles in the ACCUMULATOR CHAMBER as well as on the electrostatic panels wash out easily through the drainage ports in the frame. For tough dirt and grease, use a mild detergent (i.e., 409 or Simple Green) and rinse thoroughly with warm water. If the filter has a directional air flow arrow label on the frame, rinse the filter by back flushing it in the opposite direction of the air flow arrow for best results.



## DUSTEATER® & LIFESTYLE PLUS® FILTERS DUSTPLUS® Filter (Permanent Parts Only)

Permatron takes pride in the quality and workmanship of our products. All are built to give years of trouble-free service. Any filter found to be defective in workmanship or materials, when returned to Permatron shipping charges prepaid, will be repaired or replaced without charge. The warranty period begins from the date of purchase and does not cover damage caused by excessive heat, disassembly, rough handling or improper installation. DO NOT take the unit apart for cleaning, as this is unnecessary. With proper care and regular cleaning, your Permatron filter should last many years. Permatron Corporation makes no medical or health claims other than that the filter will effectively remove particles from the air.

1-800-882-8012 <u>www.permatron.com</u> sales@permatron.com

- Obtain a RETURN AUTHORIZATION NUMBER from Permatron Corporation Customer Service Department by calling toll-free or e-mail
- Wrap/box your filter accordingly and mail/UPS FREIGHT PREPAID to:

Permatron Corporation 2020 Touhy Avenue Elk Grove Village, IL 60007



Permatron takes pride in the quality and workmanship of our products. All are built to give years of trouble-free service. Any filter found to be defective in workmanship or materials, when returned to Permatron shipping charges prepaid, will be repaired or replaced without charge. The warranty period begins from the date of purchase and does not cover damage caused by excessive heat, disassembly, rough handling or improper installation. DO NOT take the unit apart for cleaning, except to replace DustPlus back panel, as this is unnecessary. With proper care and regular cleaning, your Permatron filter should last many years. Permatron Corporation makes no medical or health claims other than that the filter will effectively remove particles from the air.

## 1-800-882-8012 www.permatron.com

© 2010 Permatron Corporation



DISPOSABLE ODOR/FUME REMOVING REPLACEMENT PANELS

Permatron takes pride in the quality and workmanship of our products. All are built to give trouble-free service. Any filter found to be defective in workmanship or materials, when returned to Permatron shipping charges prepaid, will be repaired or replaced without charge. The warranty period begins from the date of purchase and does not cover damage caused by excessive heat, disassembly, rough handling or improper installation. DO NOT take this disposable filter apart for cleaning. With proper care your Permatron odor removing air filter could last up to six months. Permatron Corporation makes no medical or health claims other than that this filter will effectively remove odors/fumes from the air.

Your disposable filter adsorbs odor like a sponge soaks up water. Odors are pulled by molecular action into tiny pores of Carbon/Zeolite coated media. Odors are not masked with another odor, but removed from the circulated air. A portion of the air is purified on each pass through. Air velocity, humidity, type/level of odor present can influence how much is adsorbed on each pass. For best results, there must be recirculation of air through the filter. Once filter media is saturated with contaminants, it must be replaced. Substrate media has been impregnated with a finely ground coating of Activated Carbon or Zeolite, and heat set to fix it on the media. Filter can be vacuum or water-rinsed of dust, and the coating will not wash out because of bonding process. DO NOT USE ANY DETERGENT ON THIS PANEL OF FILTER.